

ROADX TR528 R³ PREMIUM TRAILER

SMARTWAY VERIFIED TIRE



SIZE	P.R.	T.D.	L.I.	S.S.	O.D.	S.W.	S.L.R.	R.W.	L.C.C.@PSI	L.C.C.@PSI
									1X	2X
11R22.5	14	12	144/142	M	41.5	11.0	19.3	8.25	6175@105	5840@105
11R24.5	14	12	146/143	M	43.5	11.0	20.3	8.25	6610@105	6005@105
295/75R22.5	14	12	144/141	M	40.0	11.7	18.7	9.00	6175@110	5675@110
285/75R24.5	14	12	144/141	M	41.3	11.1	19.4	8.25	6175@110	5675@110

The Roadx TR528 R³ is designed specifically for trailer applications. The TR528 R³ is engineered with an advanced rubber compound which delivers excellent tread wear and fuel saving performance. The TR528 R³'s tread design resists irregular wear and minimizes skid wear. Its wide center groove features "stone ejectors" to prevent stone drilling thereby extending tire life and improving retreadability. SmartWay verified tires can improve fuel efficiency by 3 per cent or more.

APPLICATIONS

- Tandem Axle Trailers
- Single Axle Trailers

TIRE FEATURES

- 1 Shallow tread reduces irregular wear.
- 2 Optimized casing reduces rolling resistance.
- 3 Solid shoulder ribs minimize skid wear.

