

DBR88

PREMIUM REGIONAL DRIVE

Part No.	Size	P.R.	T.D.	L.I.	S.S.	O.D.	S.W.	SLR	R.W.	L.C.C. (1X)	L.C.C. (2X)
DBR8821	11R22.5	14	26	144/142	M	41.5	10.9	19.5	8.25	6175@105	5840@105
DBR8822	11R22.5	16	26	146/143	M	41.5	10.9	19.5	8.25	6610@120	6005@120
DBR8820	295/75R22.5	14	26	144/141	M	40.2	10.8	20.2	9.00	6175@110	5675@110
DBR8823	11R24.5	14	26	146/143	M	43.5	10.9	20.5	8.25	6610@105	6005@105
DBR8824	11R24.5	16	26	149/146	M	43.5	10.9	20.5	8.25	7160@120	6610@120
DBR8826	285/75R24.5	14	26	144/141	M	41.3	10.8	19.6	8.25	6175@110	5675@110

The Diamondback DBR88 features an aggressive, open shoulder tread design optimized for regional applications. The DBR88 delivers exceptional traction in mud and snow. The center interlocking tread blocks provide superior stability. The DBR88 is engineered with a deep 26/32nd tread depth that results in excellent tread life.

APPLICATIONS:

- Regional Trucks
- Refuse Trucks
- Dump Trucks
- Mixed Concrete Trucks

