



BF155 FST

The Blacklion BF155 FST regional steer features a broad 5 rib tread pattern to provide precise handling and excellent stability. Wide circumferential grooves efficiently evacuate water from the tread area. The BF155 FST is ideally suited for regional applications, pick-up & delivery and limited highway service. ST sizes featuring all steel construction are specifically designed for use in specialty trailer applications.

APPLICATIONS

- Regional Trucks
- Dump Trucks
- Refuse Trucks
- Pick-up & Delivery Trucks
- Intrastate & Local Buses

TIRE FEATURES

- SmartWay verified tires can improve fuel efficiency by 3 percent or more.
- Broad 5 rib design delivers precise handling.
- Wide circumferential grooves deliver exceptional wet traction.



SMARTWAY VERIFIED TIRE

Size	Ply	T.D.		Load Index		S.R.	O.D.	S.W.	R.W.	Load Carrying Capacity		A.P.
		32nds		Single	Dual					in.	in.	
ST235/80R16**	14	10		129	125	L	30.8	9.3	6.5	4,080	3,640	110
ST235/85R16**	14	12		132	127	L	31.7	9.3	6.5	4,400	3,860	110
11R22.5	14	18		144	142	L	41.5	11.0	8.25	6,175	5,840	105
11R22.5	16	18		146	143	L	41.5	11.0	8.25	6,610	6,005	120
*12R22.5	16	18		150	147	L	42.7	11.8	9.00	7,390	6,780	120
295/75R22.5	14	18		144	141	L	39.9	11.7	8.25	6,175	5,675	110
*315/80R22.5	18	18		154	151	L	42.4	12.3	9.00	8,270	7,610	120
*315/80R22.5	20	18		156	153	L	42.4	12.3	9.00	8,820	8,045	125
11R24.5	14	18		146	143	L	43.5	11.0	8.25	6,610	6,005	105
11R24.5	16	18		149	146	L	43.5	11.0	8.25	7,160	6,610	120
285/75R24.5	14	18		144	141	L	41.3	11.1	8.25	6,175	5,675	110

**This tire size is not SmartWay® Verified ** All steel construction specifically designed for Trailer application only. Requires special high load capacity wheel. Consult wheel manufacturer for proper application. Tread may differ from image shown.