



BT166 FST

The Blacklion BT166 FST is designed specifically for trailer applications. The BT166 FST is engineered with an advanced rubber compound which delivers excellent tread wear and fuel saving performance. The BT166 FST tread design resists irregular tread wear and minimizes skid wear. Its wide center groove delivers superior water evacuation.

APPLICATIONS

- Long-Distance Trailers (Tandem)

TIRE FEATURES

- SmartWay verified tires can improve fuel efficiency by 3 percent or more.
- Shallow tread reduces irregular wear.
- Optimized casing reduces rolling resistance.
- Solid shoulder ribs minimize skid wear.



SMARTWAY VERIFIED TIRE

Size	Ply	T.D.		Load Index		S.R.	O.D.	S.W.	R.W.	Load Carrying Capacity		A.P.
		32nds		Single	Dual					in.	in.	
11R22.5	14	12		144	142	L	41.5	11.0	8.25	6,175	5,840	105
*255/70R22.5	16	12		140	137	M	36.6	10.0	7.50	5,510	5,070	120
295/75R22.5	14	12		144	141	L	39.9	11.7	8.25	6,175	5,675	110
11R24.5	14	12		146	143	L	43.5	11.0	8.25	6,610	6,005	105
285/75R24.5	14	12		144	141	L	41.3	11.1	8.25	6,175	5,675	110

* Tire size is not SmartWay® Verified